

Sand or Gravel

Safety Data Sheet

1. Product & Company Identification

Other means of identification

Natural Sand, Gravel, Sand & Construction Aggregate **Synonyms**

Recommended use Sand and Gravel aggregate may be used in the manufacture of bricks,

mortar, cement, concrete, plasters, paving materials, and other

construction materials. Sand and Gravel aggregate may be distributed in

bags, totes, and bulk shipments. Applies to all gradations.

Recommended restrictions None known. Manufacturer information/Supplier/Distributor information: Company

imi Aggregates

Division of Irving Materials, Inc.

Address 8032 N State Road 9, Greenfield, IN 46140

Telephone (317) 326-3101 Website www.irvmat.com

Normal Hours of Operation 8:00 AM to 5:00 PM Monday thru Friday

2. Hazard(s) Identification

Physical hazards Not classified.

Health hazards Category 1A Carcinogenicity

Specific Target Organ Toxicity, Category 2

repeated exposure

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer. May cause damage to organs (lung) through

prolonged or repeated exposure.

Precautionary statements

Prevention Obtain special instruction before use. Do not handle until all safety

precautions have been read and understood. Wear protective

gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Restrict or control access to stockpile areas. Engulfment hazard: to

prevent burial or suffocation, do not enter a confined space, such as a silo, bulk truck or other storage container or vessel that stores or contains aggregates without an effective procedure for assuring safety.

Disposal Dispose of contents/container in accordance with

local/regional/national/international regulations.

imi Aggregates Division of Irving Materials, Inc.

Page 1 of 8

Hazard(s) not otherwise classified Supplemental information

Special protective equipment and precautions for firefighters

Firefighting equipment/instructions

None known.

Respirable Crystalline Silica (RCS) may cause cancer. Sand & gravel is a naturally occurring mineral complex that contains varying quantities of quartz (crystalline silica). In its natural bulk state, sand & gravel is not a known health hazard. Sand & gravel may be subjected to various natural or mechanical forces that produce small particles (dust) which may contain respirable crystalline silica (particles less than 10 micrometers in aerodynamic diameter). Repeated inhalation of respirable crystalline silica may cause lung cancer according to IARC and NTP and ACGIH states that it is a suspected cause of cancer. Other forms of RCS (e.g. tridymite and cristobalite) may also be present or formed under certain industrial processes.

3. Composition/information on ingredients

Mixtures				
Chemical name	CAS number	%		
Sand and Gravel	None	>99		
Crystalline Silica (Quartz)	14808-60-7	>1		
4. First-aid measures				
Inhalation	Sand & Gravel dust: Move to fresh air. Call a physician if symptoms develop or persist.			
Skin contact	Sand & Gravel dust: Wash off with soap and water. Get medical attention if irritation develops and persists.			
Eye contact	Sand & Gravel dust: Immediately flush with plenty of water for at least 15 minutes. Hold eyelids apart. Occasionally lift the eyelid(s) to ensure thorough rinsing. Beyond flushing, do not attempt to remove material from the eye(s). Get medical attention if irritation develops or persists.			
Ingestion	Sand & Gravel dust: Rinse mouth and drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention.			
Most important symptoms/effects	Inhaling dust may cause discomfort in the chest, shortness of breath, and coughing.			
Acute and delayed	Prolonged inhalation may cause chronic health effects. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica liberated from this product can cause silicosis, and may cause cancer.			
Indication of immediate medical attention and special treat- ment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.			
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Pre-existing medical conditions that may be aggravated by exposure include disorders of the eye, skin and lung (including asthma and other breathing disorders). If addicted to tobacco, smoking will impair the ability of the lungs to clear themselves of dust.			
5. Fire-fighting measures				
Suitable extinguishing media	Sand & Gravel is not fland appropriate for surroun	ammable. Use fire extinguishing media ading materials.		
Unsuitable extinguishing media	None known.			
Specific chemical hazards	No unusual fire or explosion hazards noted. Not a combustible dust.			

imi Aggregates Division of Irving Materials, Inc. Page 2 of 8

No specific precautions.

Use protective equipment appropriate for surrounding materials.

Specific methods Contact with powerful oxidizing agents may cause fire and/or explosions

(see section 10 of SDS).

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, and emergency procedures

Methods and materials for containment and cleaning up

Wear appropriate protective equipment and clothing during clean-up of materials that contain or may liberate sand & gravel dust.

Spilled material, where dust is generated, may overexpose cleanup personnel to respirable crystalline silica containing dust. Do not dry sweep or use compressed air for clean-up. Wetting of spilled material and/or use of respiratory protective equipment may be necessary.

Avoid discharge of fine particulate matter into drains or water courses.

7. Handling and storage

Environmental precautions

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Keep formation of airborne dust to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage

Avoid dust formation or accumulation.

8. Exposure Controls/Personal protection

Occupational exposure limits

- 1 Value equivalent to OSHA formulas (29 CFR 1910.1000; 29 CFR 1917; 29 CFR 1918)
- 2 Value also applies to MSHA Metal/Non-Metal (1973 TLVs at 30 CFR 56/57.5001).
- 3 OSHA enforces 0.250 mg/m³ in construction and shipyards (CPL-03-00-007).
- 4 Value also applies to OSHA construction (29 CFR 1926.55 Appendix A) and shipyards (29 CFR 1915.1000, Table Z).
- $5 MSHA limit = 10 mg/m^3$.

U.S. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Particulates not otherwise classified	PEL	5 mg/m ³	Respirable fraction
(CAS SEQ250)		15 mg/m ³	Total dust (4)

U.S. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Crystalline Silica (Quartz) (CAS 14808-60-7)	TWA	0.3 mg/m ³ 0.1 mg/m ³	Total dust (1,2) Respirable (1,2,3)
Tridymite and Cristobalite (others forms of crystalline silica) (CAS Mixture)	TWA	0.15mg/m ³ 0.05 mg/m ³	Total dust (1) Respirable (1,2)
Particulates not otherwise classified (CAS SEQ250)	TWA	5 mg/m ³ 15 mg/m ³	Respirable fraction (1) Total dust (1,4,5)

U.S. ACGIH Threshold Limit Values®

Components	Type	Value	Form
Crystalline Silica (all forms; CAS mixture)	TWA	0.025 mg/m ³	Respirable fraction
Particulates not otherwise classified (CAS SEQ 250)	TWA	3 mg/m³ 10 mg/m³	Respirable particles (2) Inhalable particles (2)

imi Aggregates Division of Irving Materials, Inc. Page 3 of 8

U.S NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form	
Crystalline Silica (all forms; CAS mixture)	TWA	0.05mg/m ³	Respirable dust	_

Biological limit value No biological exposure limits noted for the ingredient(s).

Exposure quidelinesOSHA PELs, MSHA PELs, and ACGIH TLVs are 8-hr TWA values.

NIOSH RELs, MSHA PELS, and ACGIH TLVs are 8-hr TWA values.

NIOSH RELs are for TWA exposures up to 10-hr/day and 40-hr/wk.

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. Terms including "Particulates Not Otherwise Classified", "Particulates Not Otherwise Regulated", "Particulates Not Otherwise Specified", and "Inert or Nuisance Dust" are often used interchangeably; however, the user should review each agency's terminology for differences in meanings.

Appropriate engineering controlsGood general ventilation (typically 10 air changes per hour indoors)

should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain

airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand ProtectionOtherUse personal protective equipment as required.Use personal protective equipment as required.

Respiratory protection When handling or performing work with sand & gravel that produces

dust or respirable crystalline silica in excess of applicable exposure limits, wear a NIOSH-approved respirator that is properly fitted and is in good condition. Respirators must be used in accordance with all

applicable workplace regulations.

Thermal hazards Not anticipated. Wear appropriate thermal protective clothing, when

necessary.

General hygiene considerations Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove

contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.

Form Solid, particles.

Color Gray, brown and variations of gray and brown.

Odor Not applicable.
Odor threshold Not applicable.

pH Varies between 7.0 to 8.0

Melting point/freezing pointNot applicable.Initial boiling point and boiling rangeNot applicable.Flash pointNon-combustible.Evaporation rateNot applicable.FlammabilityNot applicable.

Upper/lower flammability or explosive

limits Not applicable.

imi Aggregates Division of Irving Materials, Inc. Page 4 of 8 Vapor pressureNot applicable.Vapor densityNot applicable.

Relative density Varies from 85 lbs/ft³ to 115 lbs/ft³

Solubility(ies) (water)

Partition coefficient (n-octanol/water)

Auto-ignition temperature

Decomposition temperature

Viscosity

Insoluble.

Not applicable.

Not applicable.

Not applicable.

Not applicable.

Other information

Explosive propertiesNot applicable. **Flammability**Not applicable.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use,

storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactionsNo dangerous reaction known under conditions of normal use.

11. Toxicological information

Information on likely routes of exposure

Inhalation Repeated inhalation of respirable crystalline silica (quartz) may cause

silicosis, a fibrosis (scarring) of the lungs. Silicosis is irreversible and may

be fatal. Silicosis increases the risk of contracting pulmonary

tuberculosis. Some studies suggest that repeated inhalation of respirable crystalline silica may cause other adverse health effects including lung

and kidney cancer.

Skin contactSand & gravel dust may cause irritation through mechanical abrasion.Eye contactSand & gravel dust causes irritation through mechanical abrasion.IngestionNot likely due to the form of the product. However, accidental ingestion

of sand & gravel may cause discomfort.

Symptoms related to the physical,

chemical and toxicological

characteristics

Sand & gravel dust: discomfort in the chest. Shortness of breath,

coughing.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Skin corrosion/irritation This product is not expected to be a skin hazard.

Serious eye damage/irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitizationNo respiratory sensitizing affects known. **Skin sensitization**Not known to be a dermal irritant or sensitizer.

Germ cell mutagenicity

No data available to indicate product or any components present at

greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Respirable crystalline silica has been classified by IARC and NTP as

known human carcinogen, and classified by ACGIH as a suspected

human carcinogen.

IARC Monographs - Overall Evaluation of Carcinogenicity

Crystalline Silica (Quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

Respirable Tridymite and Cristobalite 1 Carcinogenic to humans. (other forms of Crystalline) (CAS mixture)

imi Aggregates Division of Irving Materials, Inc. Page 5 of 8

NTP Report of Carcinogens

Crystalline Silica (Quartz) (CAS 14808-60-7)

Known to be human carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1000-1050)

None listed.

Reproductive toxicity

Specific target organ toxicity - single exposure

Specific target organ toxicity - repeated exposure

Not classified.

Respirable crystalline silica may cause damage to organs (lung) through prolonged or repeated

Not expected to be a reproductive hazard.

exposure.

Aspiration hazard Due to the physical form of the product it is not

an aspiration hazard.

Chronic effects Prolonged inhalation of respirable crystalline

silica may be harmful as it may cause damage to organs (lung) through prolonged or repeated exposure. There are reports in the literature suggesting that excessive crystalline silica exposure may be associated with autoimmune disorders and other adverse health effects involving the kidney. In particular, the incidence of scleroderma (thickening of the skin caused by swelling and thickening of fibrous tissue) appears to be higher in silicotic individuals. To date, the evidence does not conclusively determine a causal relationship between silica exposure and these adverse health effects.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms. Discharging sand

and gravel dust and fines into water may increase total suspended

particulate (TSP) levels that can be harmful to certain aquatic organisms.

Persistence and degradability

Bioaccumulative potential

Mobility in soil

Not applicable. Not applicable.

Not applicable.

Other adverse effects No other adverse environmental effects are expected from this material.

13. Disposal considerations

Disposal instructions Do not allow fine particulate matter to drain into sewers/water supplies.

Do not contaminate ponds, waterways or ditches with fine particulates.

Dispose of contents in accordance with local/regional/national/

international regulations.

Hazardous waste code Not regulated.

Waste from residue/unused products Dispose of in accordance with local regulations. Empty containers or

> liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label

warnings even after container is emptied. Empty packaging materials should be recycled or disposed of in accordance with applicable

regulations and practices.

14. Transport information

DOT Not regulated as dangerous goods. **IATA** Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and IBC Code

Not applicable.

imi Aggregates Division of Irving Materials, Inc. Page 6 of 8

15. Regulatory information

U.S. federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, subpart D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1000.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)
Superfund Amendments and Reauthorization Act of 1986 (SRAR)

Hazard categories Immediate hazard – No.

Delayed hazard – Yes. Fire hazard – No. Pressure hazard – No. Reactivity hazard – No.

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

Yes.

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act Section 112r Accidental Release Prevention (40 CFR 68.130) Safe Drinking Water Act (SDWA)B

Not regulated. Not regulated.

U.S. State regulations

Massachusetts RTK - Substance List

Crystalline Silica (Quartz) (CAS 14808-60-7)

Respirable Tridymite and Cristobalite (other forms of crystalline silica) (CAS Mixture)

U.S. New Jersey Worker and Community Right-to-Know Act

Crystalline Silica (Quartz) (CAS 14808-60-7)

Respirable Tridymite and Cristobalite (other forms of crystalline silica) (CAS Mixture)

U.S. Pennsylvania Worker and Community Right-to-Know Law

Crystalline Silica (Quartz) (CAS 14808-60-7)

Respirable Tridymite and Cristobalite (other forms of crystalline silica) (CAS Mixture)

U.S. Rhode Island RTK

Not regulated.

U.S. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

U.S. California Proposition 65 – Carcinogens & Reproductive Toxicity (CRT):

Listed substance: Crystalline Silica (Quartz) (CAS 14808-60-7)

International Inventories

Country(s) or Region Inventory name

On inventory (yes/no)*

United States & Puerto Rico

Toxic Substance Control Act (TSCA) Inventory

Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date June 1, 2015

Version # 1

For Further Information Contact: Irving Materials, Inc.

8032 N State Road 9 Greenfield, IN 46140

(317) 326-3101

imi Aggregates Division of Irving Materials, Inc. Page 7 of 8 **Notice to reader:** To the best of our knowledge, the information contained herein is accurate. However, imi Aggregate Division of Irving Materials, Inc., nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein we cannot guarantee that these are the only hazards that exist.

This Safety Data Sheet represents ingredients and values typical for sand & gravel aggregates. The information contained in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The information set forth herein is intended for use by persons having technical skill and at their own discretion and risk. Since condition of use are outside the sand & gravel products producer's control, the producer makes no warranties, expressed or implied, and assumes no liability in connection with any use of this information.

The provision of the information contained herein is not intended to be and should not be construed as legal advice or as ensuring compliance with any Federal, State, or Local laws and regulations. Any party using this product should review all such laws, rules, and/or regulations prior to use.

NO WARRANTY IS MADE, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OTHERWISE.