



Material Safety Data Sheet

Effective Date: 09-09-02

Replaces: 11-01-96

"We're Proud of Our Work"

1 – IDENTIFICATION

Natural Sand or Gravel

also called: Sand or Gravel & Construction Aggregate
Applies to all gradations

2 – PRODUCT AND COMPONENT DATA

Component(s) Limits	Chemical Name	CAS Registry	% (approx)	Exposure
Natural Sand* or Gravel*		None	100	See section 6
*Composition varies naturally typically contains quartz (crystalline silica)		14808-60-7	>0.1	

3 – PHYSICAL DATA

Appearance and Odor: Angular or round multicolored particles. No odor.
Specific Gravity: 2.55 – 2.80
Boiling Point (at 1 Atmosphere): Not Applicable **Vapor Density in Air (Air = 1):** Not Applicable
Vapor Pressure (mmHg @ 20°C): 0 **% Volatile, By Volume:** 0
Evaporation Rate (at 1Atm, and 25 C; n-butyl acetate = 1): Negligible **Solubility in Water:** 0

4 – REACTIVITY DATA

Stability: Stable **Conditions to Avoid:** Avoid contact with incompatible materials (see below).
Incompatibility (Materials to Avoid): Contact with powerful oxidizing agents such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride may cause fire and/or explosion. Silica dissolves readily in hydrofluoric acid producing a corrosive gas – silicon tetrafluoride.
Hazardous Decomposition Products: Silica-containing respirable dust particles may be generated by handling.
Hazardous Polymerization: Not known to polymerize.

5 – FIRE AND EXPLOSION HAZARD DATA

Flashpoint (Method Used): Not flammable **Flammable Limits in Air:** Not flammable
Extinguishing Agents: None required
Unusual Fire and Explosion Hazards: Contact with powerful oxidizing agents may cause fire and/or explosions (see Section 4 of this MSDS).

6 – TOXICITY AND FIRST AID

Exposure Limits (When exposure to this product and other chemicals is concurrent, the exposure limit must be defined in the workplace.): Unless specified otherwise, limits are expressed as eight-hour time-weighted averages (TWA). Limits for cristobalite and tridymite (other forms of crystalline silica) are equal to one-half of the limits for quartz.

Abbreviations: TLV = threshold limit value of the American Conference of Governmental Industrial Hygienists (ACGIH);
MSHA PEL = permissible exposure limit of the Mine Safety and Health Administration (MSHA);

OSHA PEL = permissible exposure limit of the Occupational Safety and Health Administration (OSHA);
mg/m³ = milligrams of substance per cubic meter of air.

Limestone (Calcium Carbonate) Particulates: ACGIH TLV = 10 mg/m³; OSHA PEL = 15 mg/m³ (total dust); OSHA PEL = 5 mg/m³ (respirable fraction), MSHA PEL = 10 mg/m³ (total dust).

Other Particulates: 2001 ACGIH TLV = 10 mg/m³ (inhalable - total particulate, not otherwise specified). 2001 ACGIH TLV = 3 mg/m³ (respirable particulate, not otherwise specified); OSHA PEL = 15 mg/m³ (total particulate, not otherwise regulated), OSHA PEL = 5 mg/m³ (respirable particulate, not otherwise regulated).

Respirable Crystalline Silica (SiO₂ (quartz)): ACGIH TLV = 0.05 mg/m³; MSHA and OSHA PEL = 10 mg/m³ ÷ (%SiO₂ + 2), for respirable dust containing crystalline silica.

Total dust, respirable and non-respirable: 1973 ACGIH TLV = 30 mg/m³ ÷ (%quartz + 3).

Total Dust: MSHA PEL = 10 mg/m³ (for nuisance particulates listed in Appendix E of the 1973 ACGIH TLV booklet)

Per ACGIH, adverse effects are not likely to occur in the workplace provided exposure levels do not exceed the appropriate TLVs & PELs. However, because of the wide variation in individual susceptibility, lower exposure limits may be appropriate for some individuals including persons with pre-existing medical conditions such as those described below.

Medical Conditions Aggravated by Exposure: Inhaling respirable dust and/or crystalline silica may aggravate existing respiratory system disease(s) and/or dysfunction. Exposure to dust may aggravate existing skin and/or eye conditions.

Primary Route(s) of Exposure:

Inhalation Skin Ingestion

Acute Toxicity:

Eye Contact: Direct contact with dust may cause irritation by mechanical abrasion.
Skin Contact: Direct contact may cause irritation by mechanical abrasion.
Skin Absorption: Not expected to be a significant exposure route.
Ingestion: Expected to be practically non-toxic. Ingestion of large amounts may cause gastrointestinal irritation and blockage.
Inhalation: Dusts may irritate the nose, throat, and respiratory tract by mechanical abrasion. Coughing, sneezing, and shortness of breath may occur following exposures in excess of appropriate exposure limits.

First Aid:

Eyes: Immediately flush eye(s) with plenty of clean water for at least 15 minutes, while holding the eyelid(s) open. Occasionally lift the eyelid(s) to ensure thorough rinsing. Beyond flushing, do not attempt to remove material from the eye(s). Contact a physician if irritation persists or later develops.
Skin: Wash with soap and water. Contact a physician if irritation persists or later develops.
Ingestion: If person is conscious, give large quantity of water and induce vomiting; however, never attempt to make an unconscious person drink or vomit. Get immediate medical attention.
Inhalation: Move to fresh air. Dust in throat and nasal passages should clear spontaneously. Contact a physician if irritation persists or later develops.

Chronic Toxicity: Prolonged and repeated inhalation of respirable crystalline silica containing dust in excess of appropriate exposure limits has caused silicosis, a lung disease. Not all individuals with silicosis will exhibit symptoms (signs) of the disease. However, silicosis can be progressive, and symptoms can appear at any time, even years after exposure has ceased. Symptoms of silicosis may include, but are not limited to, the following: shortness of breath; difficulty breathing with or without exertion; coughing; diminished work capacity; diminished chest expansion; reduction of lung volume; right

heart enlargement and/or failure. Smoking may increase the risk of developing lung disorders, including emphysema and lung cancer. Persons with silicosis have an increased risk of pulmonary tuberculosis infection.

Respirable dust containing newly broken silica particles has been shown to be more hazardous to animals in laboratory tests than respirable dust containing older silica particles of similar size. Respirable silica particles which had aged for sixty days or more showed less lung injury in animals than equal exposures of respirable dust containing newly broken particles of silica.

There are reports in the literature suggesting that excessive crystalline silica exposure may be associated with adverse health effects involving the kidney, scleroderma (thickening of the skin caused by swelling and thickening of fibrous tissue) and other autoimmune disorders. However, this evidence has been obtained primarily from case reports involving individuals working in high exposure situations or those who have already developed silicosis; and therefore, this evidence does not conclusively prove a causal relationship between silica or silicosis and these adverse health effects. Several studies of persons with silicosis also indicate an increased risk of developing lung cancer, a risk that increases with the duration of exposure. Some of these studies of silicotics do not account for lung cancer confounders, especially smoking.

Natural Sand & Gravel is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). In October 1996, an IARC Working Group re-assessing crystalline silica, a component of this product, designated respirable crystalline silica as carcinogenic (Group 1). The NTP's Report on Carcinogens, 9th Edition, lists respirable crystalline silica as a "known human carcinogen". In year 2000, the American Conference of Governmental Industrial Hygienists (ACGIH) listed respirable crystalline silica (quartz) as a suspected human carcinogen (A-2). These classifications are based on sufficient evidence of carcinogenicity in certain experimental animals and on selected epidemiological studies of workers exposed to crystalline silica.

California Proposition 65:

WARNING: This product contains chemical(s) known to the State of California to cause cancer.

7 – PERSONAL PROTECTION AND CONTROLS

Respiratory Protection: For respirable quartz levels that exceed or are likely to exceed an 8-hr TWA of 0.1 mg/m³, a NIOSH approved dust respirator is recommended. For respirable quartz levels that exceed or are likely to exceed an 8-hr TWA of 0.5 mg/m³, a NIOSH approved HEPA filter respirator is recommended. If respirable quartz levels exceed or are likely to exceed an 8-hr TWA of 5 mg/m³, a NIOSH approved positive pressure, full face respirator or equivalent is recommended. Respirator use must comply with applicable MSHA or OSHA standards, which include provisions for a user training program, respirator repair and cleaning, respirator fit testing, and other requirements.

Ventilation:

Local exhaust or general ventilation adequate to maintain exposures below appropriate exposure limits.

Skin Protection: See "Hygiene" section below

Eye Protection: Safety glasses with side shields should be worn as minimum protection. Dust goggles should be worn when excessively (visible) dusty conditions are present or are anticipated.

Hygiene: Wash dust exposed skin with soap and water before eating, drinking, smoking, and using toilet facilities. Wash work clothes after each use.

Other Control Measures: Respirable dust and quartz levels should be monitored regularly. Dust and quartz levels in excess of appropriate exposure limits should be reduced by all feasible engineering controls, including (but not limited to) wet suppression, ventilation, process enclosure, and enclosed employee work stations.

8 – STORAGE AND HANDLING PRECAUTIONS

Respirable crystalline silica containing dust may be generated during processing, handling, and storage. The personal protection and controls identified in Section 7 of this MSDS should be used as appropriate. Do not store near food and beverages or smoking materials.

9 – SPILL, LEAK, AND DISPOSAL PRACTICES

Steps to be taken in case material is released or spilled: The personal protection and controls identified in Section 7 of this MSDS should be used as appropriate. Spilled material, where dust can be generated, may overexpose cleanup personnel to respirable crystalline silica containing dust. Wetting of spilled material and/or use of respiratory protective equipment may be necessary. Do not dry sweep spilled material. Prevent spilled materials from inadvertently entering streams, drains, or sewers.

Waste Disposal Method: Pick up and reuse clean materials. Dispose of waste materials only in accordance with applicable Federal, State, and Local laws and regulations.

10 – TRANSPORTATION

DOT Hazard Classification: None

Placard Required: None

Label Required: Label as required by the OSHA Hazard Communication Standard [29CFR 1910.1200 (f)] and applicable State and Local laws and regulations.

For Further Information Contact: Irving Materials, Inc.
8032 N State Road 9
Greenfield, IN 46140
(317) 326-3103

Emergency Contact: Walter E. Tharp, Safety Director
(317) 432-9604

Notice: Irving Materials, Inc. believes the information contained herein is accurate; however Irving Materials, Inc. makes no guarantees with respect to such accuracy and assumes no liability in connection with the use of the information contained herein by any party. The provision of the information contained herein is not intended to be and should not be construed as legal advice or as ensuring compliance with any Federal, State, or Local laws and regulations. Any party using this product should review all such laws, rules, and/or regulations prior to use.

NO WARRANTY IS MADE, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OTHERWISE.