

H1BAK1347 NAPA Lith-Ease Grease (Plastic Tub 1 pound) 765-1393

=====

MATERIAL SAFETY DATA SHEET

Effective Date: 9-6-94 Revision Date:
none

NAPA Lith-Ease Grease (Plastic Tub 1 pound) 765-1393
Code: AGS
Page: 1

=====

Section 1 - Product and Company Identification

PRODUCT NAME: NAPA Lith-Ease Grease (Plastic Tub 1 pound) 765-1393

MANUFACTURER'S NAME: EMERGENCY TELEPHONE
NUMBER (800)255-3924
AGS Company
2651 Hoyt St.
Muskegon Hts. , MI 49444 MISCELLANEOUS
INFORMATION (616)733-2101

=====

Section 2 - Hazardous Ingredients

HAZARDOUS INGREDIENT	CAS NO.	WGT. %	TLV
White Lithium Grease	Not Assigned	100%	5 cu. m.

NOTE:

=====

Section 3 - Hazards Indentification

EYES: May cause irritation.

SKIN: May cause irritation on prolonged or repeated contact.

INGESTION: Contains petroleums, may cause diarrhea and nausea.

INHALATION: When at elevated temperature or aerosolized, may cause irritation of the respiratory tract.

OTHER EFFECTS: Not known.

=====

Section 4 - First Aid Measures

EYES: Flush with water for at least 15 minutes. Call a physician

immediately.

SKIN: Wash thoroughly with soap and water.

INGESTION: Do not induce vomiting. Call a physician immediately.

INHALATION: Of oil mist from grease; remove victim to fresh air.
Administer oxygen or artificial respiration as required.
Consult a physician.

=====

MATERIAL SAFETY DATA SHEET

Effective Date: 9-6-94
none

Revision Date:

NAPA Lith-Ease Grease (Plastic Tub 1 pound) 765-1393

Code: AGS

Page: 2

=====

Section 5 - Firefighting Measures

FLASH POINT : 400F
METHOD : C.O.C.
AUTO IGNITION TEMP: Not Determined

FLAMMABLE LIMITS:
LEL: Not Determined
UEL: Not Determined

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, foam, water fog,
sand or
earth.

SPECIAL PROCEDURES: Wear self-contained breathing apparatus.

UNUSUAL HAZARDS: Dense smoke.

=====

Section 6 - Environmental Release Measures

SPILL PROCEDURE: Transfer bulk of material to a container. Remove the
residue with an absorbent material.

=====

Section 7 - Handling and Storage

CONDITIONS TO AVOID: None listed.

=====

Section 8 - Exposure Controls/Personal Protection

VENTILATION REQUIREMENTS: General exhaust exceptable where a TLV of 5
cu.

m. as mineral oil will not be exceeded.

EYES : Yes
GLOVES : Yes
CLOTHING : No
RESPIRATORY: No

OTHER: Eye wash in work area.

=====

MATERIAL SAFETY DATA SHEET

Effective Date: 9-6-94 Revision Date:
none

NAPA Lith-Ease Grease (Plastic Tub 1 pound) 765-1393

Code: AGS
Page: 3

=====

Section 9 - Physical and Chemical Properties

pH SUPPLIED : Not Applicable
pH DILUTED : Not Applicable
WATER SOLUBILITY: Nil
SPECIFIC GRAVITY: (Water=1) 0.90
MELTING POINT : 360F (min.)
BOILING POINT : Not Applicable
% VOLATILES : Not Applicable
VAPOR PRESSURE : Not Applicable
VAPOR DENSITY : Not Applicable
EVAPORATION RATE: Not Applicable
APPEARANCE : Pale yellow semi-solid with mineral oil odor.

=====

Section 10 - Stability and Reactivity

UNSTABLE AND/OR AUTO REACTIVE: Stable
INCOMPATIBLE MATERIALS: Strong oxidizing agents.
HAZARDOUS DECOMPOSITION PRODUCTS: CO and carbon dioxide.

=====

Section 11 - Toxicological Information

Not available.

=====

Section 12 - Ecological Information

Not available.

=====

Section 13 - Disposal Considerations

DISPOSAL METHOD: Removal by an approved, licensed waste hauler.

EPA WASTE I.D. NO.: Not Reg.

=====
Section 14 - Transport Information

Not available.

=====
Section 15 - Regulatory Information

Not available.

=====
MATERIAL SAFETY DATA SHEET

Effective Date: 9-6-94
none

Revision Date:

NAPA Lith-Ease Grease (Plastic Tub 1 pound) 765-1393

Code: AGS

Page: 4

=====
Section 16 - Other Information

TRADE NAME : NAPA White Lithium Grease
COMMON NAME : Lith-Ease
CONATINER SIZE: Plastic Tube, 1 pound

NFPA: HEALTH : 0
FLAMMABILITY : 1
REACTIVITY : 0
SPECIFIC HAZARD: N/A

HMIS: HEALTH : 0
FLAMMABILITY : 1
REACTIVITY : 0
PROTECTIVE EQUIPMENT: A

***The information herein is given in good faith,
no warranty, expressed or implied, is made.***