

Material Safety Data Sheet

1. MATERIAL AND COMPANY IDENTIFICATION

Material Name : Shell Morlina S4 B 150
 Uses : Gear lubricant.
 Manufacturer/Supplier : Shell Oil Products US
 PO BOX 4453
 Houston, TX 77210-4453
 USA
 MSDS Request : 877-276-7285
 Emergency Telephone Number : 877-242-7400
 Spill Information :
 Health Information :

2. COMPOSITION/INFORMATION ON INGREDIENTS

Blend of polyolefins and additives.
 The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.
 The highly refined mineral oil is only present as additive diluent.

3. HAZARDS IDENTIFICATION

Appearance and Odour	Emergency Overview
Health Hazards	Yellow. Liquid at room temperature. Slight hydrocarbon.
Safety Hazards	Not classified as dangerous for supply or conveyance.
Environmental Hazards	Not classified as flammable but will burn.
	Not classified as dangerous for the environment.

Health Hazards : Not expected to be a health hazard when used under normal conditions.
 Health Hazards : Under normal conditions of use, this is not expected to be a primary route of exposure.
 Inhalation : Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.
 Skin Contact : May cause slight irritation to eyes.
 Eye Contact : Low toxicity if swallowed.
 Ingestion : Used oil may contain harmful impurities.
 Other Information : Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas.
 Signs and Symptoms : Ingestion may result in nausea, vomiting and/or diarrhoea.
 Aggravated Medical Conditions : Pre-existing medical conditions of the following organ(s) or material: Skin
 Environmental Hazards : Not classified as dangerous for the environment.

Material Safety Data Sheet

Additional Information : Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

4. FIRST AID MEASURES

General Information : Not expected to be a health hazard when used under normal conditions.
 Inhalation : No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
 Skin Contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
 Eye Contact : Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
 Ingestion : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
 Advice to Physician : Treat symptomatically.

5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

Flash point : Typical 238 °C / 457 °F (COC)
 Upper / lower : Typical 1 - 10 %(V)
 Flammability or :
 Explosion limits :
 Auto Ignition temperature : > 320 °C / 608 °F
 Specific Hazards : Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.
 Suitable Extinguishing Media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
 Unsuitable Extinguishing Media : Do not use water in a jet.
 Protective Equipment for Firefighters : Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.

6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe the relevant local and international regulations.

Protective measures : Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
 Clean Up Methods : Slippery when split. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or

Material Safety Data Sheet

- Additional Advice** : other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly. Local authorities should be advised if significant spillages cannot be contained.
- 7. HANDLING AND STORAGE**
- General Precautions** : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
- Handling** : Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used.
- Storage** : Keep container tightly closed and in a cool, well-ventilated place. Use property labelled and closable containers. Storage Temperature: 0 - 50 °C / 32 - 122 °F
- Recommended Materials** : For containers or container linings, use mild steel or high density polyethylene.
- Unsuitable Materials** : PVC.
- Additional Information** : Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

Occupational Exposure Limits

Material	Source	Type	ppm	mg/m ³	Notation
Oil mist, mineral	ACGIH	TWA (inhalable fraction)		5 mg/m ³	
Oil mist, mineral	OSHA Z1	PEL (Mist)		5 mg/m ³	
Oil mist, mineral	OSHA Z1A	TWA (Mist)		5 mg/m ³	

- Additional Information** : Shell has adopted as Interim Standards the OSHA Z1A values that were established in 1989 and later rescinded.
- Exposure Controls** : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
- Personal Protective** : Personal protective equipment (PPE) should meet

Material Safety Data Sheet

- Equipment Respiratory Protection** : recommended national standards. Check with PPE suppliers. No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >85°C (148 °F)].
- Hand Protection** : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. Wear safety glasses or full face shield if splashes are likely to occur.
- Eye Protection** : Skin protection not ordinarily required beyond standard issue work clothes.
- Protective Clothing** : Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.
- Environmental Exposure Controls** : Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance** : Yellow. Liquid at room temperature.
- Odour** : Slight hydrocarbon.
- pH** : Not applicable
- Initial Boiling Point and Boiling Range** : > 280 °C / 536 °F estimated value(s)
- Pour point** : Typical -54 °C / -65 °F
- Flash point** : Typical 236 °C / 457 °F (COC)
- Upper / lower Flammability or Explosion limits** : Typical 1 - 10 % (V)
- Auto-ignition temperature** : > 320 °C / 608 °F
- Vapour pressure** : < 0.5 Pa at 20 °C / 68 °F (estimated value(s))
- Specific gravity** : Typical 0.848 at 15 °C / 59 °F

Material Safety Data Sheet

Density : Typical 848 kg/m³ at 15 °C / 59 °F
 Water solubility : Negligible.
 n-octanol/water partition coefficient (log Pow) : > 6 (based on information on similar products)
 Kinematic viscosity : Typical 150 mm²/s at 40 °C / 104 °F
 Vapour density (air=1) : > 1 (estimated value(s))
 Evaporation rate (EiUA=C=1) : Data not available

10. STABILITY AND REACTIVITY

Stability : Stable.
 Conditions to Avoid : Extremes of temperature and direct sunlight.
 Materials to Avoid : Strong oxidising agents.
 Hazardous Decomposition Products : Hazardous decomposition products are not expected to form during normal storage.

11. TOXICOLOGICAL INFORMATION

Basis for Assessment : Information given is based on data on the components and the toxicology of similar products.
 Acute Oral Toxicity : Expected to be of low toxicity: LD50 > 5000 mg/kg. Rat
 Acute Dermal Toxicity : Expected to be of low toxicity: LD50 > 5000 mg/kg. Rabbit
 Acute Inhalation Toxicity : Not considered to be an inhalation hazard under normal conditions of use.
 Skin Irritation : Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.
 Eye Irritation : Irritation of vapours or mists may cause irritation.
 Respiratory Irritation : Inhalation of vapours or mists may cause irritation.
 Sensitisation : Not expected to be a skin sensitiser.
 Repeated Dose Toxicity : Not expected to be a hazard.
 Mutagenicity : Not considered a mutagenic hazard.
 Carcinogenicity : Components are not known to be associated with carcinogenic effects.
 Reproductive and Developmental Toxicity : Not expected to be a hazard.
 Additional Information : Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible.

12. ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.
 Acute Toxicity : Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be practically non toxic. LL₅₀/LL₅₀ > 100 mg/l (to aquatic organisms) (LL₅₀ expressed as the

Material Safety Data Sheet

nominal amount of product required to prepare aqueous test extract).
 Mobility : Liquid under most environmental conditions. Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile.
 Persistence/degradability : Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.
 Bioaccumulation : Contains components with the potential to bioaccumulate.
 Other Adverse Effects : Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

13. DISPOSAL CONSIDERATIONS

Material Disposal : Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.
 Container Disposal : Dispose in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
 Local Legislation : Disposal should be in accordance with applicable regional, national, and local laws and regulations.

14. TRANSPORT INFORMATION

US Department of Transportation Classification (48CFR)
 This material is not subject to DOT regulations under 49 CFR Parts 171-180.

IMDG

This material is not classified as dangerous under IMDG regulations.
 IATA (Country variations may apply)
 This material is not classified as dangerous under IATA regulations.

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Federal Regulatory Status

Notification Status

EINECS : All components listed or

Shell Morlina S4 B 160
MSDS# 16965EU
Version 1.0
Effective Date 03/04/2011
According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

Material Safety Data Sheet

TSCA
DSL
polymer exampl.
All components listed.
All components listed.

Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

SARA Hazard Categories (311/312)
No SARA 311/312 Hazards.

State Regulatory Status

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

This material does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

16. OTHER INFORMATION

NFPA Rating (Health, Fire, Reactivity) : 0, 1, 0
MSDS Version Number : 1.0
MSDS Effective Date : 03/04/2011
MSDS Revisions : A vertical bar (|) in the left margin indicates an amendment from the previous version.
MSDS Regulation : The content and format of this MSDS is in accordance with the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
MSDS Distribution : The information in this document should be made available to all who may handle the product.
Disclaimer : The information contained herein is based on our current knowledge of the underlying data and is intended to describe the product for the purpose of health, safety and environmental requirements only. No warranty or guarantee is expressed or implied regarding the accuracy of these data or the results to be obtained from the use of the product.

Shell Morlina S4 B 160
MSDS# 16965EU
Version 1.0
Effective Date 03/04/2011
According to OSHA Hazard Communication Standard, 29 CFR
1910.1200

Material Safety Data Sheet