

DOW CORNING(R) 890-SL SELF-LEVELING SILICONE JOINT SEALANT**1. PRODUCT AND COMPANY IDENTIFICATION**

Dow Corning Corporation
South Saginaw Road
Midland, Michigan 48686

24 Hour Emergency Telephone: (989) 496-5900

Customer Service: (989) 496-6000

Product Disposal Information: (989) 496-6315

CHEMTREC: (800) 424-9300

MSDS No.: 02265796

Revision Date: 2009/10/23

Generic Description: Silicone elastomer

Physical Form: Liquid

Color: Charcoal

Odor: Amine-like odor

NFPA Profile: Health 2 Flammability 1 Instability/Reactivity 0

Note: NFPA = National Fire Protection Association

2. HAZARDS IDENTIFICATION**POTENTIAL HEALTH EFFECTS****Acute Effects**

Eye: Direct contact may cause moderate irritation.

Skin: May cause mild irritation.

Inhalation: Irritates respiratory passages very slightly.

Oral: Low ingestion hazard in normal use.

Prolonged/Repeated Exposure Effects

Skin: Repeated or prolonged exposure may irritate seriously.

Inhalation: Overexposure by inhalation may injure the following organ(s): Testes. Liver. Pancreas. Spleen.

Oral: Overexposure by ingestion may injure the following organ(s): Pancreas. Liver. Spleen. Testes.

Signs and Symptoms of Overexposure

No known applicable information.

Medical Conditions Aggravated by Exposure

No known applicable information.

DOW CORNING(R) 890-SL SELF-LEVELING SILICONE JOINT SEALANT

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
50791-87-2	1.0 - 5.0	Methylvinyl bis(n-methylacetamido) silane
68952-53-4	1.0 - 5.0	Dimethyl, methylethyl-N-hydroxyethamine siloxane

The above components are hazardous as defined in 29 CFR 1910.1200.

4. FIRST AID MEASURES

Eye:	Immediately flush with water for 15 minutes. Get medical attention.
Skin:	Remove from skin and wash thoroughly with soap and water or waterless cleanser. Get medical attention if irritation or other ill effects develop or persist.
Inhalation:	Remove to fresh air. Get medical attention if ill effects persist.
Oral:	Get medical attention.
Notes to Physician:	Treat according to person's condition and specifics of exposure.

5. FIRE FIGHTING MEASURES

Flash Point:	212 °F / 100 °C (Pensky-Martens Closed Cup)
Autoignition Temperature:	Not determined.
Flammability Limits in Air:	Not determined.
Extinguishing Media:	On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO ₂), dry chemical or water spray. Water can be used to cool fire exposed containers.
Fire Fighting Measures:	Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.
Unusual Fire Hazards:	None.

6. ACCIDENTAL RELEASE MEASURES

DOW CORNING(R) 890-SL SELF-LEVELING SILICONE JOINT SEALANT

Containment/Clean up: Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protection equipment recommendations described in Sections 5 and 8. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbant. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Note: See section 8 for Personal Protective Equipment for Spills. Call (989) 496-5900, if additional information is required.

7. HANDLING AND STORAGE

Use with adequate ventilation. Product evolves N-methyl acetamide when exposed to water or humid air. Provide ventilation during use to control N-methyl acetamide within exposure guidelines or use respiratory protection. Avoid eye contact. Avoid skin contact. Avoid breathing vapor, mist, dust, or fumes. Keep container closed. Do not take internally.

Keep container closed and store away from water or moisture.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Component Exposure Limits**

<u>CAS Number</u>	<u>Component Name</u>	<u>Exposure Limits</u>
50791-87-2	Methylvinyl bis(n-methylacetamido) silane	See N-methyl acetamide comments.

N-methyl acetamide is formed on contact with water or humid air. Provide adequate ventilation to control exposures to within Dow Corning recommended exposure guidelines of 1 ppm (TWA) and 5 ppm (Excursion Limit).

Engineering Controls

Local Ventilation: Recommended.
General Ventilation: Recommended.

Personal Protective Equipment for Routine Handling

Eyes: Use proper protection - safety glasses as a minimum.

DOW CORNING(R) 890-SL SELF-LEVELING SILICONE JOINT SEALANT

Skin:	Wash at mealtime and end of shift. If skin contact occurs, change contaminated clothing as soon as possible and thoroughly flush affected areas with cool water. Chemical protective gloves are recommended.
Suitable Gloves:	Avoid skin contact by implementing good industrial hygiene practices and procedures. Select and use gloves and/or protective clothing to further minimize the potential for skin contact. Consult with your glove and/or personnel protective equipment manufacturer for selection of appropriate compatible materials.
Inhalation:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. IH personnel can assist in judging the adequacy of existing engineering controls.
Suitable Respirator:	General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.

Personal Protective Equipment for Spills

Eyes:	Use full face respirator.
Skin:	Wash at mealtime and end of shift. If skin contact occurs, change contaminated clothing as soon as possible and thoroughly flush affected areas with cool water. Chemical protective gloves are recommended.
Inhalation/Suitable Respirator:	Respiratory protection recommended. Follow OSHA Respirator Regulations (29 CFR 1910.134) and use NIOSH/MHSA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.
Precautionary Measures:	Avoid eye contact. Avoid skin contact. Avoid breathing vapor, mist, dust, or fumes. Keep container closed. Do not take internally. Use reasonable care.
Comments:	Product evolves N-methyl acetamide when exposed to water or humid air. Provide ventilation during use to control N-methyl acetamide within exposure guidelines or use respiratory protection.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions. For further information regarding aerosol inhalation toxicity, please refer to the guidance document regarding the use of silicone-based materials in aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Liquid

DOW CORNING(R) 890-SL SELF-LEVELING SILICONE JOINT SEALANT

Color: Charcoal
 Odor: Amine-like odor
 Specific Gravity @ 25°C: 1.3
 Viscosity: 300000 cSt

Freezing/Melting Point: Not determined.
 Boiling Point: > 35 °C
 Vapor Pressure @ 25°C: Not determined.
 Vapor Density: Not determined.
 Solubility in Water: Not determined.
 pH: Not determined.
 Volatile Content: Not determined.
 Flash Point: 212 °F / 100 °C (Pensky-Martens Closed Cup)
 Autoignition Temperature: Not determined.
 Flammability Limits in Air: Not determined.

Note: The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

10. STABILITY AND REACTIVITY

Chemical Stability: Stable.

Hazardous Polymerization: Hazardous polymerization will not occur.

Conditions to Avoid: None.

Materials to Avoid: Water, moisture, or humid air can cause hazardous vapours to form as described in Section 8 . Oxidizing material can cause a reaction.

Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Metal oxides. Carbon oxides and traces of incompletely burned carbon compounds. Quartz. Formaldehyde. Silicon dioxide. Nitrogen oxides.

11. TOXICOLOGICAL INFORMATIONComponent Toxicology Information

Contains Bis(N-methyl acetamido)silane which liberates N-methylacetamide (NMA) during cure. NMA has been shown to cause birth defects in laboratory animals.

Special Hazard Information on Components

DOW CORNING(R) 890-SL SELF-LEVELING SILICONE JOINT SEALANT

No known applicable information.

12. ECOLOGICAL INFORMATION**Environmental Fate and Distribution**

Complete information is not yet available.

Environmental Effects

Complete information is not yet available.

Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.

Ecotoxicity Classification Criteria

Hazard Parameters (LC50 or EC50)	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	<=1	>1 and <=100	>100
Acute Terrestrial Toxicity	<=100	>100 and <= 2000	>2000

This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993.

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

13. DISPOSAL CONSIDERATIONS**RCRA Hazard Class (40 CFR 261)**

When a decision is made to discard this material, as received, is it classified as a hazardous waste? No

State or local laws may impose additional regulatory requirements regarding disposal. Call (989) 496-6315, if additional information is required.

14. TRANSPORT INFORMATION**DOT Road Shipment Information (49 CFR 172.101)**

Not subject to DOT.

Ocean Shipment (IMDG)

Not subject to IMDG code.

Air Shipment (IATA)

DOW CORNING(R) 890-SL SELF-LEVELING SILICONE JOINT SEALANT

Not subject to IATA regulations.

Call Dow Corning Transportation, (989) 496-8577, if additional information is required.

15. REGULATORY INFORMATION

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

EPA SARA Title III Chemical Listings**Section 302 Extremely Hazardous Substances (40 CFR 355):**

None.

Section 304 CERCLA Hazardous Substances (40 CFR 302):

None.

Section 311/312 Hazard Class (40 CFR 370):

Acute: Yes
Chronic: Yes
Fire: No
Pressure: No
Reactive: No

Section 313 Toxic Chemicals (40 CFR 372):

None present or none present in regulated quantities.

Note: Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.

Supplemental State Compliance Information**California**

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

None known.

Massachusetts

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
471-34-1	30.0 - 60.0	Calcium carbonate

DOW CORNING(R) 890-SL SELF-LEVELING SILICONE JOINT SEALANT

New Jersey

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
70131-67-8	40.0 - 70.0	Dimethyl siloxane, hydroxy-terminated
471-34-1	30.0 - 60.0	Calcium carbonate
63148-62-9	10.0 - 30.0	Polydimethylsiloxane
50791-87-2	1.0 - 5.0	Methylvinyl bis(n-methylacetamido) silane
68952-53-4	1.0 - 5.0	Dimethyl, methylethyl-N-hydroxyethamine siloxane
14808-60-7	<1.0	Quartz

Pennsylvania

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
70131-67-8	40.0 - 70.0	Dimethyl siloxane, hydroxy-terminated
471-34-1	30.0 - 60.0	Calcium carbonate
63148-62-9	10.0 - 30.0	Polydimethylsiloxane

16. OTHER INFORMATION

Prepared by: Dow Corning Corporation

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

(R) indicates Registered Trademark